


## Stock No.555

### Steel straight edge normal form

- These straightedges are optimal for scribing.
- Two types (Hardened, Without hardening) are available.
- The accuracy of one side is guaranteed. (Side A)



#### Configuration of stock number



Material : S50C

Package: Carton (150 ~ 600 mm)

Wooden box(750mm~)

Product No	Stock No	L (mm)	W (mm)	T (mm)	Straightness (μm)	Weight (kg)
41-1-0150	555-0150Q	150	25	3	13.0	0.08
41-2-0150	555-0150					
41-1-0200	555-0200Q	200	25	3	14.0	0.11
41-2-0200	555-0200					
41-1-0250	555-0250Q	250	30	4	15.0	0.3
41-2-0250	555-0250					
41-1-0300	555-0300Q	300	35	5	16.0	0.4
41-2-0300	555-0300					
41-1-0450	555-0450Q	450	40	5	19.0	0.7
41-2-0450	555-0450					
41-1-0500	555-0500Q	500	40	5	20.0	0.8
41-2-0500	555-0500					
41-1-0600	55-0600Q	600	40	5	22.0	0.9
41-2-0600	555-0600					
41-1-0750	555-0750Q	750	50	6	25.0	1.7
41-2-0750	555-0750					
41-1-1000	555-1000Q	1,000	50	6	30.0	2.6
41-2-1000	555-1000					
41-1-1500	555-1500Q	1,500	75	6	40.0	5.8
41-2-1500	555-1500					
41-1-2000	555-2000Q	2,000	85	8	50.0	11.0
41-2-2000	555-2000					
41-1-2500	555-2500Q	2,500	90	10	60.0	19.0
41-2-2500	555-2500					
41-1-3000	555-3000Q	3,000	100	10	70.0	24.0
41-2-3000	555-3000					


## Stock No.555B

### Steel straight edge bevel form

- These straightedges are optimal for scribing.
- Two types (Hardened, Without hardening) are available.
- The accuracy of one side (Side A) is guaranteed.



#### Configuration of stock number



Material : S50C

Package: Carton (150 ~ 600 mm)

Wooden box(750mm~)

Product No	Stock No	L (mm)	W (mm)	T (mm)	Straightness (μm)	Weight (kg)
40-1-0150	555-0150BQ	150	25	3	13.0	0.08
40-2-0150	555-0150B					
40-1-0200	555-0200BQ	200	25	3	14.0	0.1
40-2-0200	555-0200B					
40-1-0250	555-0250BQ	250	30	4	15.0	0.3
40-2-0250	555-0250B					
40-1-0300	555-0300BQ	300	35	5	16.0	0.4
40-2-0300	555-0300B					
40-1-0450	555-0450BQ	450	40	5	19.0	0.7
40-2-0450	555-0450B					
40-1-0500	555-0500BQ	500	40	5	20.0	0.8
40-2-0500	555-0500B					
40-1-0600	555-0600BQ	600	40	5	22.0	0.9
40-2-0600	555-0600B					
40-1-0750	555-0750BQ	750	50	6	25.0	1.6
40-2-0750	555-0750B					
40-1-1000	555-1000BQ	1,000	50	6	30.0	2.5
40-2-1000	555-1000B					
40-1-1500	555-1500BQ	1,500	75	6	40.0	5.5
40-2-1500	555-1500B					
40-1-2000	555-2000BQ	2,000	85	8	50.0	10.5
40-2-2000	555-2000B					
40-1-2500	555-2500BQ	2,500	90	10	60.0	18.0
40-2-2500	555-2500B					
40-1-3000	555-3000BQ	3,000	100	10	70.0	23.5
40-2-3000	555-3000B					