

フランジ付リニアベアリング

—シングルタイプ—

dr 許容差	D 許容差	L 許容差	D1	T	d	d1	H1	P.C.D	K	F	A	偏芯	直角度	基本定格荷重		質量(g)		
														C(動)N	Co(静)N	丸フランジ	角フランジ	二面フランジ
6		12 0 19	28	5	3.5	6	3.1	20	22	-	20			206	265	24	18	21
8		15 -0.013 24	32					24	25	-	24			274	392	37	29	33
10	0	19	40					29	30	-	29	0.012	0.012	372	549	72	52	64
12	-0.009	21 0 30	42	6	4.5	7.5	4.1	32	32	-	32			510	784	76	57	68
13		23 -0.016 32	43					33	34	-	33			510	784	88	72	81
16		28	48					38	37	22	31			774	1,180	120	104	112
20	0	32 0 42	54	8	5.5	9	5.1	43	42	24	36			882	1,370	180	145	167
25	-0.010	40 -0.019 59	62					51	50	32	40	0.015	0.015	980	1,570	340	300	325
30		45	74	10	6.6	11	6.1	60	58	35	49			1,570	2,740	470	375	388
35	0	52 0 70	82					67	64	38	55			1,670	3,140	650	560	575
40	-0.012	60 -0.022 80	96	13	9	14	8.1	78	75	45	64	0.020	0.020	2,160	4,020	1,060	880	913
50		80	116					98	92	56	80			3,820	7,940	2,200	2,000	2,037

注:カッコ内は互換性品

注文例 Catalog No.
FLT8