

# フランジ付リニアベアリング

—ロングスリーブセンターフランジタイプ—

Catalog No.						D		L		ℓ	D1	T	d	d1	H1	P.C.D	K	F	A	偏芯	直角度	
品名						dr	許容値	許容値	許容値													
丸フランジ		角フランジ		二面フランジ		6		15		50												
SUJ2	SUS440C	SUJ2	SUS440C	SUJ2	SUS440C	8	0	19	0	70												
						10	-0.009	23	-0.021	80											0.020	0.020
						12		26		85												
						16		32	0	100												
FLDLC	MFLDLC	FLDLKC	MFLDLKC	FLDLTC	MFLDLTC	20	0	40	-0.025	120											0.025	0.025
(LHKMRL)		(LHKMSL)		(LHKMLL)		25	-0.010	45		165												
						30		52	0	180												
									-0.030													

注:①カッコ内は互換性品

②FLDLC6.8、FLDLKC6.8、FLDLTC6.8、MFLDLC6.8、MFLDLKC6.8、MFLDLTC6.8グリースニップルなし。

dr	基本定格荷重		質量(g)		
	C(動)N	Co(静)N	丸フランジ	角フランジ	二面フランジ
6	323	530	70	60	—
8	431	784	140	120	—
10	588	1,100	210	190	—
12	813	1,570	250	230	—
16	1,230	2,350	420	380	390
20	1,400	2,740	760	720	730
25	1,560	3,140	1,250	1,170	1,180
30	2,490	5,490	1,640	1,550	1,570

注文例 Catalog No.  
FLDLKC20