

# フランジ付リニアベアリング（回転直線無限運動軸受）

—ダブルタイプ—

| Catalog No. |       |    |        | D   |        | L   |      | D1 | T  | d   | d1  | H1  | P.C.D | K  | 許容回転<br>(rpm) |
|-------------|-------|----|--------|-----|--------|-----|------|----|----|-----|-----|-----|-------|----|---------------|
| 品 名         |       | dr | 許容値    | 許容値 |        | 許容値 |      |    |    |     |     |     |       |    |               |
| FDCR        | FDCRK | 8  | +0.008 | 19  | 0      | 52  | ±0.3 | 40 | 7  | 4.5 | 7.5 | 4.4 | 29    | 30 | 300           |
|             |       | 10 | 0      | 21  | -0.021 | 58  |      | 42 | 7  | 4.5 | 7.5 | 4.4 | 32    | 32 | 300           |
|             |       | 12 | +0.009 | 22  |        | 68  |      | 42 | 7  | 4.5 | 7.5 | 4.4 | 32    | 32 | 300           |
|             |       | 16 | -0.001 | 28  |        | 76  |      | 50 | 9  | 5.5 | 9   | 5.4 | 38    | 38 | 250           |
|             |       | 20 | +0.011 | 40  | 0      | 94  |      | 64 | 11 | 6.6 | 11  | 6.1 | 51    | 50 | 250           |
|             |       | 25 | -0.001 | 45  | -0.025 | 118 |      | 76 | 12 | 9   | 14  | 8.1 | 60    | 60 | 250           |
|             |       | 30 |        | 52  |        | 138 |      | 84 | 12 | 9   | 14  | 8.1 | 67    | 64 | 200           |
|             |       |    |        |     |        |     |      |    |    |     |     |     |       |    |               |

| dr | 基本定格荷重  |          | 質量 (g) |       |
|----|---------|----------|--------|-------|
|    | C (動) N | Co (静) N | 丸フランジ  | 角フランジ |
| 8  | 216     | 451      | 60     | 50    |
| 10 | 314     | 746      | 80     | 62    |
| 12 | 549     | 1,177    | 100    | 80    |
| 16 | 902     | 1,765    | 200    | 170   |
| 20 | 1,099   | 2,353    | 680    | 600   |
| 25 | 1,765   | 3,726    | 1,000  | 920   |
| 30 | 2,314   | 5,295    | 1,200  | 1,120 |

注文例 Catalog No.  
FDCR8