

フランジ付リニアブロック

—軽量ダブルタイプ—

Catalog No.			D		L		D1	T	P.C.D	K	取付		グリースニップル
品名	dr	許容値		許容値		許容値					S1	S2	
FLWT (丸形)	6	0	20	0	46	±0.3	38	7	30	30	M5	M4	—
FLWTK (角形)	8		24	-0.021	56		44	7	35	35	M5	M4	
FLWTG (丸形・ニップル付)	10		30		68		52	8	42	42	M5	M4	
FLWTKG (角形・ニップル付)	12		34		70		54	8	45	44	M5	M4	
ステンレスベアリング	13	-0.009	34	0	70		54	8	45	44	M5	M4	
MFLWT (丸形)	16		42	-0.025	88		72	9	58	58	M8	M6	A-M6×1
MFLWTK (角形)	20		48		98		78	10	64	62	M8	M6	
MFLWTG (丸形・ニップル付)	25		58	0	134		90	11	76	72	M8	M6	
MFLWTKG (角形・ニップル付)	30	-0.010	65	-0.030	144		104	12	86	84	M10	M8	
	40		84	0	178		124	14	106	100	M10	M8	
		-0.012		-0.035									

dr	基本定格荷重		質量 (g)	
	C (動) N	Co (静) N	丸フランジ	角フランジ
6	323	530	50	50
8	431	784	90	90
10	588	1,100	160	150
12	813	1,570	190	170
13	813	1,570	200	180
16	1,230	2,350	370	340
20	1,400	2,740	510	460
25	1,560	3,140	1,020	940
30	2,490	5,490	1,440	1,300
40	3,430	8,040	2,750	2,560

注文例 Catalog No.
FLWT6