

フランジ付リニアブロック —軽量ロングスリーブタイプ—

Catalog No.			L		D	C	D0	D1	T	B	P.C.D	K	S	取付	
品名	dr	許容値			許容値									S1	S2
FLWL (丸形) FLWLK (角形) FLWL B (丸形・インロー) FLWLKB (角形・インロー) ステンレスベアリング MFLWL (丸形) MFLWLK (角形) MFLWL B (丸形・インロー) MFLWLKB (角形・インロー)	16	$0_{-0.009}$	150	45	0	22	44	80	11	20	60	60	7	M8	M6
	20		150	50	-0.025	24	49	90	12	20	70	66	9	M10	M8
			200							30					
	25	0	200	60	0	30	59	100	15	30	80	74	11	M12	M10
		-0.010	250							40					
			200		-0.030					30					
	30		250	70		36	69	120	18	40	100	90	11	M12	M10
			300							50					
			250							40					
	40	0	300	90	0	40	89	160	20	50	130	126	14	M14	M12
		-0.012	300		-0.035					50					
	50		350	120		40	119	190	20	60	160	150	14	M14	M12

※フェルトシールも両端に取付けられる構造になっています。(ダブルシール型)

dr	L	基本定格荷重		質量 (Kg)	
		C (動) N	Co (静) N	丸フランジ	角フランジ
16	150	1,230	2,350	0.5	0.48
20	150	1,400	2,740	0.6	0.58
	200			0.8	0.78
25	200	1,560	3,140	1.0	0.97
	250			1.6	1.57
30	200	2,490	5,490	1.5	1.45
	250			2.0	1.95
	300			2.5	2.45
40	250	3,430	8,040	4.0	3.93
	300			4.5	4.43
50	300	6,080	15,900	8.0	7.92
	350			8.5	8.42

注文例 Catalog No.
FLWL20-200